



MAYOR GLUE

MULTI-PURPOSE WHITE GLUE

Description **MAYOR GLUE** is Multi-Purpose White Glue is a versatile, general-purpose, polyvinyl acetate woodworking adhesive. It is particularly suited for high strength, permanent bonding on wood and a variety of other porous materials.

Uses **MAYOR GLUE** Bonding porous substrates such as wood, wood compositions, veneer, paper, cardboard, leather, fabric and cork.
Mayor Glue is ideal for creating the tight fitting joints required in quality indoor wood working projects. It allows for the repair of lifted edges of wall paper or carpet.
Mix with sawdust and use as a wood or wallboard filler. Use to seal or prime porous surfaces.

- Advantages**
- Easy removal once cured
 - Paintable
 - Dries translucent white (Invisible glue lines)
 - Non-Toxic
 - Bond is stronger than the wood
 - Not damaged by freezing
 - Easy to handle
 - Excellent flow control

Product Data Form flowing liquid
Color White
Base PVAC
Solvent Water
application temperature above 15°C
Curing time 5 minutes
Open time 5 minutes
Backing 1kg, 5 kg
Shelf life 24 months from date of manufacture (unopened)
Storage Condition Store in a dry, safe place. Do not store in environments where extreme temperatures may occur. Keep within 5-30°C. Do not store in direct sunlight



APPLICATION DETAILS **MAYOR GLUE** was developed as a wood adhesive for interior and exterior applications in areas not exposed to direct weather conditions.

DIRECTION For hart wood apply one layer from mayor , glue for highly porous substrates apply two layers. After application of the advise a minimum pressure time of 10 minutes after application get rid of any residue . Staining of the adhesive can stay visible after being painted over with transparent paint

LIMITATION

- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates
- Not suitable for wood with a moisture content above 15%

SURFACE PREPARATIONS AND FINISHING Application temperature: +5°C to +45°C (applies to environment and substrates). All substrates must be solid, clean, dry, and free of grease and dust. Always test adhesion prior to application.

CLEANING It is possible the adhesive will remain visible after painting with transparent paint.

SAFETY Non-hazardous. Ensure good ventilation. Keep out of reach of children. Contact with eyes-wash immediately with warm water. Remove excess from tools and mixing vessels before washing in warm soapy water. Do not empty containers into drains or watercourses.

+249-912981928
+249-918883330
+249-929888333

✉ husam@mayoreng.com

مصنع مابور لكيمائيات البناء
مابور كيم

🌐 www.mayoreng.com

+249-9183478259

📍 المصنع: المنطقة الصناعية الباكير مربع (1) - عقار رقم ٦٦
الإدارة: الخرطوم تقاطع شارع الصحافة زلط مع شارع ١٥
العمارات - عمارة مابور الطابق الأول