



MAYOR CRACKS REPAIR

Filler for suoface cracks of concrete

Description Mayor cracks repair is restoration and hepair graut ready mixed, modified with high flowability polymers

- Advantages**
- Suitable for repair inclined morvar cracks in concrete
 - High flowaloolity
 - Easy application
 - increase freeze,thaw cycling resistance and penetrate in hair cracks
 - increase impact resistance
 - improve five resistance properties

- USES**
- Treatment of surface cracks

Product Date **Form:** grey powder
Packaging: 10 kg bag
Shelf Life : 24 months unopend original container

Storage corditions It shoud be stored in dry and cool area, protected from direct sunlight

Technical Data It complies with ASTM C1107
Chloride content : Nil
Compressive strength (N/mm2)
3days = 20
7 days = 24
At 28 days=35
Linear shrinkage
At 3 days =0.01%
At 7 days : 0.01%

Application Details Substrate shoud be cleane, free from all dust, dirt, oil, grease and any particle which could affect the bonding.
Before applying Mayor cracks repair substrate should be moistured for 12 hours, this procedures is essential in hot weather



Product Preparation

Mayor cracks repair is mixed with water according the purpose of using either manually or mechanically by electric mixer in which proudt should be mixed for three minutes to avoid lump formation 20 - 30 minutes after mixing depending on ambientand surface cenditions

Note : Freshly applied Mayor cracks repair should be protected from water for 12 house at least

Safety precaution

It is preferable to apply product in good ventilated area
suitalde protective clotling, gloves, goggles and mask are recommended during application
stain on the skin shallbe washed splashed into eyes, wash immediately with plenty of water

Don't dispose of into water or soil, but according to local regulations.